

VAISALA

Order form

Purchaser

Valid from March 2014

Order no

Vaisala HUMICAP® Digital Humidity Module HMM105

Digital Humidity Module		HMM105		1	2	3	4	5	6	7	8	PRICE
1	Output signal	I <sup>2</sup> C output only		A								
2	Probe type	Plastic, 0.3 m flex cable	-40°C ...+180°C	1								
3	Humidity sensor type	General purpose	HUMICAP180R		A							
		Extra fast response	HUMICAP180		B							
4	Sensor protection	Short PTFE sintered filter	-40...+180 °C				1					
		Plastic grid filter	-20...+80 °C				2					
		Plastic grid and membrane filter	-20...+80 °C				3					
		PTFE sintered filter	-40...+180 °C				4					
		Stainless steel sintered filter	-40...+180 °C				5					
5	Module cable	No cable			A							
		0.6 m cable w/ Molex milli-grid connector at both ends			B							
6	Packaging	Single						1				
		Multi-package (25 pcs)						2				
7	Identity	Vaisala								1		
8	Quick reference guide	None									0	
		English										E
TOTAL												
QTY												
TOTAL VALUE												

Selections in bold are included in the prices of the basic versions.  
Selections in *italic* are available at an extra price.

Example of order code with typical settings:

HMM105 A 1 A 1 A 1 1 E

End customer: \_\_\_\_\_

Spare parts:	
HUMICAP180R	Humidity sensor
DRW239993SP	Short PTFE filter
6221	Plastic grid filter
10159HM	Plastic grid and membrane filter
219452SP	PTFE filter
HM47280SP	Stainless steel sintered filter
ASM210962SP	Connection cable(0.6 m, Molex milli-grid connectors)